



DATA SHEET 

Model: ESE-G50

Color Ultrasound System



Ultrasound System Specifications

Extremely portable and exceptional performance ESE-G50 meets all your clinical needs by:

- Unmatched image quality
- All ranges of features, functions, and probes
- Flexible and customized simple workflow

System Overview

Architecture

- The revolutionary RF platform, allows for more accurate information. This platform transfers all RF data for computing without any information loss. It has a much better advantage in detail imaging than current advanced platforms
- Thanks to the RF platform, it allows the development of many RF-based processing algorithms, which have ultra-premium contrast and resolution imaging
- This unique platform is capable of processing multiple data streams simultaneously
- Up to 25MHz next generation digital broadband and high resolution acoustic beamforming
- The new 12 bit, low noise, digital circuitry, with up to 230db dynamic range has improved 2D performance and increased Doppler sensitivity
- Directional-enhanced information compiling for more tissue detail and reduction of angle-generated artifacts
- Next generation adaptive image processing for noise and artifact reduction that improves tissue presentation and edge definition
- Fully independent, triplex multiple mode operation for easy in Doppler procedures
- Multi-processors allow simultaneous mode changes and support for advanced system functionality

Applications

- | | | | |
|--------------|--------------|---------------|-------------------|
| • Abdomen | • Cardiology | • TCD | • Pediatrics |
| • Obstetric | • Urology | • Small Parts | • Intra-operative |
| • Gynecology | • Vascular | | |





Imaging features

- 2D grayscale imaging
- Harmonic imaging both in tissue harmonic and pulse inversion harmonic technologies
- VFusion, RF-based directional-enhanced information compounding
- VSpeckle, specialized and adaptive imaging processing to remove speckle noise artifacts and enhance tissue edge for clarity and accuracy
- VTissue, the advanced adaptive image processing to compensate for sound and speed variation in different tissue
- Auto imaging optimization*
- Easy Comparative Function to compare previous exam
- Tissue M-mode
- Color M-mode(optional)
- Color Doppler imaging
- Power Doppler imaging
- Pulse wave Doppler imaging
- Simultaneous 2D and M mode
- Duplex 2D/PW Doppler
- Triplex 2D/Color/PW Doppler
- High PRF pulsed wave Doppler
- Continuous wave Doppler
- RF-based Zoom
- FULL screen imaging to enlarge imaging size
- Dual real time imaging without compromising imaging size
- Multi Angle M-mode with 360 degree rotation (Optional)
- PView for panoramic imaging (Optional)
- TView for trapezoidal imaging
- Elastography imaging(Optional)
- Contrast imaging(Optional)
- 3D imaging
- 3D/4D HQR (High Quality rendering) (Optional)*
- Spatio_Temporal Image Correlation (STIC) (Optional)*
- VOCAL (Volume calculation, Follicle count) (Optional)*
- SRV (Super Resolution Volume) to have extreme contrast and resolution in thin volume
- Tomographic display (MCUT)
- Inversion mode(Optional)
- Magic Cut
- Smart Touch 3D/4D operation(Optional)
- Free View(Optional)
- Auto NT* (Optional)
- Real-time grayscale 4D
- Three leads ECG function (Optional)
- Tissue Doppler (TD) mode*
- Tissue Velocity Imaging (TVI) mode* (Optional)
- Tissue Velocity M (TVM) mode*(Optional)
- Integrated smart stress echo mode* (Optional)
- Auto IMT function*

Standard features

- Up to 25Mhz high frequency in system platform. Up to 18MHz's probes are supported
- RF platform and RF data processing
- Up to 1500 seconds standard cine storage
- 500GB hard drive
- Integrated DVDRW
- Integrated black/white thermal video printer slot
- Patient information database
- Image archive on hard drive
- Quick store to USB memory stick
- Quick store to hard drive
- Quick print to B/W and color thermal video printer
- Network storage and printing
- Full measurement and analysis package
- Real time auto wave Doppler track and calculations
- Vascular calculations
- Cardiac calculations
- OB calculations and tables
- Gynecological calculations
- Urological calculations
- Renal calculations
- Volume calculations
- Barcode reader for patient information input
- Wireless networking for easy data sharing, storage and printing (*optional*)
- Bluetooth for image data transfer (*optional*)
- Image data transfer directly by E-Mail with network access (*optional*)
- Up-to-date connectivity and data management solutions, wireless (*optional*), LAN, Bluetooth, E-Mail, integrated database
- DICOM compatibility*
- Three active probe ports, plus one dummy probe port
- 5 USB ports
- 8 TGC slides
- Average 4 multiple adjustable frequency in every probe and mode
- Up to 512 line density
- 1 DVI-D interface
- 1 Audio in interface; 1 Audio out interface
- 1 Speaker interface
- 1 RJ45 interface

Ergonomics

- Unique human oriented design for comfort and convenience
- Fully articulating 19-inch high resolution flat panel display
- Easy access DVD media drive
- 4 easy access transducer ports (three active and one dummy)
- 4 transducer holders (removable for easy cleaning)
- Integrated touchable alphabetic keyboard
- Simple, easy and effective cable management structure



Keyboard

- Highly sensitive 10 inch capacity touch panel
- Intuitive, configurable and touchable interactive operation interface
- Ergonomic hard keys for general ultrasound operations
- 8 TGC slides, functionality at any depth
- Backlight keys

Image display screen

- 19 inch high resolution IPS, LED technology
- Brightness, contrast and color temperature adjustment
- Adjustable Gamma curve optimization for dedicated applications
- Big angel swivel and tilting capability

Peripherals

- B&W thermal video printer: Sony UP-D897MD (optional)
- Color thermal video printer: Sony UP-D25MD (optional)
- Memory stick (optional)

Dimensions and Weight

- Height: 1305mm
- Width: 540mm
- Depth: 855mm
- Weight: 50kg

Electrical Power

- Voltage: 100-240V AC
- Frequency: 50/60Hz
- Power: < 470VA for console only

Transducers

Transducer Technology

- Xcen technology for wideband frequency
- Pure wave technology for high resolution imaging
- Unique and high technical Xcen probe connector to adapt all different type of product models

Transducer types

- | | | |
|----------------|---------------|----------------------|
| • Convex array | • Phase array | • Endocavity probe |
| • Linear array | • 4D probe | • Micro-convex array |

Transducer selection

- Electronic switching of transducers
- User customizable imaging presets for each transducer and application
- Automatic dynamic receiving focus in all transducers
- Multiple adjustable transmit focal zone, up to 8 focal zone

G2-5C Broadband Curved Array

- Field of view: 66 degree
- Convex radius: 50mm
- Application: abdomen, OB/Gyn, urology, pediatric
- Frequency range: 1.4 -5.6MHz
- Pulsed wave Doppler, color Doppler, power Doppler, harmonic
- Multi-imaging frequency setting in 2D, Harmonic, color Doppler and Wave Doppler modes
- Reusable biopsy guide available





F2-5C Broadband Curved Array

- Field of view: 59 degree
- Convex radius: 59.5mm
- Application: abdomen, OB/Gyn, urology, pediatric
- Frequency range: 1.6 -5.5MHz
- Pulsed wave Doppler, color Doppler, power Doppler, harmonic
- Multi-imaging frequency setting in 2D, Harmonic, color Doppler and Wave Doppler modes
- Reusable biopsy guide available

D3-6C broadband curved array volume probe

- Field of view: 78 degree
- Convex radius: 40mm
- Application: abdomen, OB/Gyn, urology
- Frequency range: 1.9 - 7MHz
- Pulsed wave Doppler, color Doppler, power Doppler, harmonic, 3D/4D grayscale
- Multi-imaging frequency setting in 2D, Harmonic, color Doppler and Wave Doppler modes

D3-6CX broadband curved array volume probe

- Footprint: 48mm
- Field of view: 75 degree
- Convex radius: 40mm
- Application: abdomen, OB/Gyn, urology
- Frequency range: 2.1 – 5.7MHz
- Pulsed wave Doppler, color Doppler, power Doppler, harmonic , 3D/4D grayscale, 3D color
- Multi-imaging frequency setting in 2D, 3D/4D, Harmonic, color Doppler and Wave Doppler modes

G4-9M broadband micro convex array

- Field of view: 138 degree
- Convex radius: 12mm
- Application: pediatric, abdomen, cardiac
- Frequency range: 3 - 10MHz
- Pulsed wave Doppler, color Doppler, power Doppler, harmonic
- Multi-imaging frequency setting in 2D, Harmonic, color Doppler and Wave Doppler modes

G4-9E broadband micro convex endocavity array

- Field of view: 138 degree
- Convex radius: 12mm
- Application: Ob/Gyn, urology
- Frequency range: 3 - 10MHz
- Pulsed wave Doppler, color Doppler, power Doppler, harmonic
- Multi-imaging frequency setting in 2D, Harmonic, color Doppler and Wave Doppler
- Reusable biopsy guide available

D4-9E broadband micro convex 4D endocavity array

- Field of view: 125 degree
- Convex radius: 10mm
- Application: Ob/Gyn, urology
- Frequency range: 3 - 10MHz
- Number of element: 128
- Pulsed wave Doppler, color Doppler, power Doppler, harmonic , 3D/4D grayscale,
- Multi-imaging frequency setting in 2D, 3D/4D, Harmonic, color Doppler and Wave Doppler modes

X4-12L broadband linear array

- Fine pitch, high resolution
- Applications: vascular, small parts
- Frequency range: 4.5 -13MHz
- Pulsed wave Doppler, color Doppler, power Doppler, harmonic
- Multi-imaging frequency setting in 2D, Harmonic, color Doppler and Wave Doppler modes

X6-16L broadband linear array

- Fine pitch, high resolution
- Applications: vascular, small parts
- Frequency range: 6.5 -18MHz
- Pulsed wave Doppler, color Doppler, power Doppler, harmonic
- Multi-imaging frequency setting in 2D, Harmonic, color Doppler and Wave Doppler modes





U5-15LE broadband linear array

- Fine pitch, high resolution
- Applications: small parts, specially for breast, vascular
- Footprint: 52mm
- Frequency range: 5 -15Mhz
- Pulsed wave Doppler, color Doppler, power Doppler, harmonic
- Multi-imaging frequency setting in 2D, Harmonic, color Doppler and Wave Doppler modes

I4-11T broadband linear array

- Fine pitch, high resolution
- Frequency range: 4.2-11Mhz
- Pulsed wave Doppler, color Doppler, power Doppler, harmonic
- Multi-imaging frequency setting in 2D, Harmonic, color Doppler and Wave Doppler modes

G1-4P phased array

- Applications: cardiac, abdomen, Ob/Gyn, Urology
- Frequency range: 1.35-4.3Mhz
- Pulsed wave Doppler, continuous wave Doppler, color Doppler, power Doppler, harmonic
- Multi-imaging frequency setting in 2D, Harmonic, color Doppler and Wave Doppler modes

S1-6P phased array

- Single Crystal technology
- Applications: cardiac, abdomen, Ob/Gyn, Urology
- Frequency range: 1.9-7Mhz
- Pulsed wave Doppler, continuous wave Doppler, color Doppler, power Doppler, harmonic
- Multi-imaging frequency setting in 2D, Harmonic, color Doppler and Wave Doppler modes

Advanced Imaging controls

VFusion

- Available on all transducers and for 2D, 3D/4D (except phase array)
- Up to 5 levels of directional imaging fusion to enrich information
- Operate in conjunction with VSpeckle, harmonic imaging

VSpeckle

- Available on all transducers and for 2D, 3D/4D
- Virtually eliminate speckle noise artifact and dynamically enhances tissue margins
- Selectable multiple levels of speckle noise reduction and smoothing
- Operates in conjunction with VFusion and harmonic imaging

VTissue *

- Advanced imaging processing to adapt to the speed of the ultrasound variation in different tissue
- Improved detail resolution and conspicuity of lesions
- Presentable sound and speed in different applications
- One touch operation to ease diagnosis

SRV (Super Resolution Volume)

- Extreme contrast and spatial resolution in thin volume
- Small volume sweep angle
- High volume rate
- Visual able the tissue information in a thick slice
- Better detection in diffuse lesions of organs



Advanced Imaging controls (cont.)

3D/4D HQR (High Quality Rendering) (Optional)

- Amazing high image quality
- Extreme realistic rendering images
- Similar operation as normal rendering

VOCAL (Volume Calculation) (Optional)

- Automatic 3D follicle detection (number&size)
- Definition of a shell contour
- Volume calculation of ultrasound tissue inside a shell contour

Spatio-Temporal Image Correlation (STIC) (Optional)

- Visualize the fetal heart or an artery
- One complete heart cycle represented
- Using 3D static acquisition

Inversion mode(Optional)

- This render mode is used to display anechoic structures such as vessels
- It invert the gray values of the rendered image, such as black image information become white and vice versa

Magic Cut

- Ability to edit images, make possible to cut away structure obstructing the view in the ROI
- Several cutting methods available

Smart Touch 3D/4D Operation(Optional)

- Fully utilize touch panel possibility for easy operation, such as rotation 3D rendering image, move ROI, create line by finger

Free View(Optional)

- Provide any plane view to visualize the internal tissue information
- Improve the contrast resolution to facilitate the detection of diffuse lesions in organs

Stress Echo (Optional)

- Review and analyze wall segment information
- Continuous capture or selectable capture
- Provides selectable protocol template for exercise

Auto NT (Nuchal Translucency) measurement (Optional)

- Automatically detect Nuchal Translucency in interest box
- Automatically report thickness result of NT

Auto IMT (Intima-Media Thickness) measurement

- Automatically detect intima media thickness in interest box
- Automatically report the result of IMT
- Available in linear probe

Next generation RF-based image processing

- Available on all imaging transducers in 2D grayscale modes
- Virtually eliminates speckle noise artifact and dynamically enhance tissue edge
- Operates with other real-time processing algorithms



Imaging modes

2D Imaging

- Pre-defined ATGC (adaptive temporal gain compensation) curves optimized for consistently excellent imaging
- B/M acoustic output: 0-100%
- Depth: able to adjust from 1 to 36cm
- Select between 1 to 8 transmit focal zones
- Reverse function: on/off
- VFusion function
- VSpeckle function
- Harmonic imaging both tissue harmonic and phase inversion
- Cineloop image review
- Selectable 2D line density
- Dual imaging with independent cineloop
- 256(8 bit) gray level
- Up to 8 focus zone adjustable
- Multiple color maps with chroma imaging
- FULL screen imaging to larger image size
- Multi frequency: probe dependent
- Gray filter: 6 steps
- Persistence: 8steps
- Selectable image angles, probe dependent
- Gain: 0-100%
- Dynamic range: 30-230 db
- VSharpen to enhance edge contrast
- Smooth to improve spatial resolution
- EdgeEnhance to improve detail information and contrast
- VNear to enhance SNR of near field

Harmonic Imaging

- Supports both tissue harmonic and phase inversion imaging (transducer and frequency dependence)
- Second harmonic processing to reduce artifacts and improve image clarity
- Maximize detail resolution and enhance contrast
- Available on all imaging transducers
- Extends high performance imaging capabilities to all patient body types

M mode

- Selectable sweeping rates
- Time marks: 0.025 – 0.5 second
- Selectable display format prospective or retrospective (1/3-2/3, 1/2-1/2, 2/3-1/3, side by side 1/2-1/2, side by side 1/3-2/3, full screen)
- Chroma colorization with multiple color maps
- Cineloop review for retrospective analysis of M-mode data
- 256 gray levels

Color Doppler mode

- Available on all imaging transducers
- Automatically adapts transmit and receive bandwidth processing based on the color box position
- Cineloop review with full playback control
- Steering on linear array transducers
- Color flow M mode display for tissue motion and flow velocity(optional)
- Selectable in baseline, line density, flash reduction, persistence, maps, frequency, PRF, wall filter, packet size, color level, sensitivity, focus position, acoustic power, and smooth
- Color gain
- Region of interest
- Baseline invert
- Simultaneous mode during PW mode
- Smoothing
- Wall filter
- Zoom

Power Doppler mode

- High sensitive mode for small vessel visualization
- Available on all transducers
- Cineloop review
- Multiple color maps
- Individual controls for gain
- Selectable baseline, line density, flash reduction, persistence, maps, frequency, PRF, wall filter, packet size, color level, sensitivity, focus position, acoustic power, and smooth
- Adjustable region of interest

Pulsed Wave (PW) Doppler

- Ultra high resolution spectral FFT rate
- Angle correction with automatic velocity scale adjustment
- Normal, invert display around horizontal zero line
- Selectable gray filter, dynamic range, frequency, PRF, wall filter, baseline, angel correct, sample volume
- Selectable sweep speeds: 8 steps
- Maximum velocity range: 12m/s
- PW acoustic output: 0-100%
- Selectable low frequency signal filtering with adjustable wall filter settings
- Selectable grayscale curve for optimal display
- Selectable chroma colorization maps
- Selectable display format prospective or retrospective (1/3-2/3, 1/2-1/2, 2/3-1/3, side by side 1/2-1/2, side by side 1/3-2/3, full screen)
- Auto function to optimize spectral Doppler displ.
- Digitally enhanced stereo output
- 256 gray levels
- Post-processing in frozen mode includes map, baseline, invert and chroma
- Simultaneous or duplex mode of operation
- Simultaneous 2D, color Doppler, pulsed Doppler
- High PRF capability in all modes including duplex and triplex





Continuous Wave Doppler (CWD)

- Cardiac sector array transducer only
- Maximum velocity range: 19m/s

Elastography imaging(Optional)

- Shows the spatial distribution of tissue elasticity properties in a region of interest to estimate the strain before and after tissue distortion caused by external force
- The strain estimation is scaled by color to have smooth distribution display
- Have quality index to indicate if there is proper external force

Contrast imaging(Optional)

- Support contrast imaging in both 2D and 3D volume
- By contrast agent, imaging is enhanced within vessel which agent flow
- Have one button push to destroy the agent. Useful in the bubble wash-in characteristics of anatomy being scanned

3D/4D

- 3D/4D rotation
- Grayscale imaging controls
- Selectable rendering approaches
- Unique high quality rendering algorithm
- Selectable gray maps
- Multi slide cutting (MCUT)
- Cineloop 3D
- Review volume

PView

- Real time extended field of view composite imaging
- Ability to back up and realign the image during acquisition
- Full zoom, cineloop review and image rotation capabilities
- User can measure distance and area
- Measurement can be made on individual frames during cineloop review
- Available on linear transducers

TView

- Expand view of scanning
- Available on linear transducers

Auto

- Intelligent one button automatic optimization in 2D and Doppler modes
- Automatically adjust PRF and baseline in Doppler

Stress Echo*

- Acquisition of single-frames or full-motion digital clips in any modes (including 2D, color flow, power Doppler, etc)
- Length of acquired images is user-adjustable
- Default stress protocols
- Flexible user defined stress protocols

Tissue Doppler Imaging (TD) *

- Present wall motion spectrum by using Doppler principle
- Provide wall motion direction and velocity information
- Available on all sector transducer for cardiac imaging
- Gain

Tissue Velocity Imaging (TVI) *

- Color codes the velocities in tissue
- Present tissue color imaging by using Doppler principle
- This color image is overlaid onto the 2D image
- Captures low flow but high amplitude signals associated with wall motion
- Available on all sector transducer for cardiac imaging
- Tissue velocity M mode display for wall motion(optional)
- Gain
- Velocity



Touch Panel Interface

2D mode

- | | | | |
|---|--|--|---|
| <ul style="list-style-type: none"> • New patient • BodyPattern • Archive • Comments • End exam • Sys setting • Probe&App • Pview • Tview • Fullscreen | <ul style="list-style-type: none"> • L/R • U/D • Center line • VTissue • VSpeckle • VFusion • Gray Filter • Persistence • Display Format • Image reference | <ul style="list-style-type: none"> • Maps • Frequency • Focus position • Focus # • Dynamic Range • Line density • VSharpen • Biopsy • Image angle | <ul style="list-style-type: none"> • Focus width • Smooth • Acoustic power • Contrast imaging • Elastosonography • EdgeEnhance • Vnear • NeedleEnhance • SGC |
|---|--|--|---|

M Mode

- | | | | |
|---|--|---|---|
| <ul style="list-style-type: none"> • New patient • BodyPattern • Archive • Comments | <ul style="list-style-type: none"> • End exam • Sys setting • Probe&App • L/R format | <ul style="list-style-type: none"> • U/D format • Maps • Dynamic range • Acoustic power | <ul style="list-style-type: none"> • Sweep speed • Gray filter • VSharpen • ECG |
|---|--|---|---|

CF mode

- | | | | |
|---|---|---|---|
| <ul style="list-style-type: none"> • New patient • BodyPattern • Archive • Comments • End exam • Sys setting • Probe&App • Invert | <ul style="list-style-type: none"> • Full Screen • L/R • U/D • Baseline • Flash Reduction • Line density • Persistence | <ul style="list-style-type: none"> • Display format • Sync display • Transparency • Image reference • Maps • Frequency • PRF | <ul style="list-style-type: none"> • Wall filter • Packet size • Colorlevel • Sensitivity • Focus position • Acoustic power • Smooth |
|---|---|---|---|

PW/CW mode

- | | | | |
|---|---|---|---|
| <ul style="list-style-type: none"> • New patient • BodyPattern • Archive • Comments • End exam • Sys setting • Probe&App | <ul style="list-style-type: none"> • Invert • Triplex • Display format • Sweep speed • Gray filter • Dynamic range • Trace sensitive | <ul style="list-style-type: none"> • Auto trace • Mode/direction • Maps • Frequency • PRF • Wall filter | <ul style="list-style-type: none"> • Baseline • Steer • Sample volume • Volume • Spectrum optimize • Acoustic power |
|---|---|---|---|

3D mode

- | | |
|---|---|
| <ul style="list-style-type: none"> • Comments • BodyPattern • Back to 2D • Start3D • Render • Display format • Image reference • View • Gray map • VSpeckle • Quality • Threshold • Transparency | <ul style="list-style-type: none"> • Volume angle • Auto rotate (after data acquisition) • Movement step (after data acquisition) • Slice position(after data acquisition) • Speed(after data acquisition) • HQ Light(after data acquisition) • Rotation angle (after data acquisition) • Rotation direction (after data acquisition) • 3DMcut(after data acquisition) • Magic Cut (after data acquisition) • Free View(after data acquisition) • Smart Touch 3D/4D operation(after data acquisition) |
|---|---|

4D mode

- | | |
|---|---|
| <ul style="list-style-type: none"> • Comments • Body Pattern • Back to 2D • Start 4D • Auto Cine • Movement step • Rotation direction • Render • Display format • Image reference | <ul style="list-style-type: none"> • View • Gray map • VSpeckle • Quality • Threshold • Transparency • Volume angle • Slice position(after data acquisition) • 3DMcut(after data acquisition) • Smart Touch 3D/4D operation(after data acquisition) |
|---|---|





System Feature

Display modes

- Simultaneous capability
- 2D/PW/CW
- 2D/CF or PDI
- 2D/M
- Dual, 2D/2D
- Dual, 2D/2D+CF or PDI
- Dual, duplex and triplax
- Duplex and Triplex mode
- Quad display in 3D/4D application
- 9 slice images display in 3D/4D application
- Time line display
- Independent dual 2D/PW or CW
- Timed based sweep update mode

Display annotation

- Institution/hospital name
- Date: 2 types selectable, YY/MM/DD, MM/DD/YY
- Time: 2 types selectable, 24hours and 12 hours
- Operator identification
- Patient name, first, last
- Patient identification: 30 characters
- Gestational age from LMP/EDC/GA/BBT
- Power output index
- MI: mechanical index
- TIS: thermal index soft tissue
- TIC: thermal index cranial (Bone)
- TIB: thermal index bone
- Probe orientation marker: coincide with a probe orientation marking on the probe
- Gray/color bar
- Measurement result window
- Probe type
- Application name
- Image depth
- Imaging parameters by mode
- 2D/M mode: acoustic power output, gain, frequency, frame rate, dynamic range
- Color mode: color acoustic power output, color gain, color flow frequency, PRF, wall filter
- PW/CW mode: Doppler acoustic power output, Doppler gain, Doppler frequency, PRF, wall filter, sample depth
- Scanline Gain Compensation(SGC) with 6 slides adjustment
- Focus zone marker
- Body pattern
- PW and CW scale markers: time/speed
- M scale markers: time/depth, time
- System measurement display
- System message display
- Biopsy guide line
- Heart rate

Simple User Operation Interface

- Simple user interface and easy workflow, allows one step on probe & application switch, and intuitive user parameter control

Cineloop

- Acquisition, storage in memory and display of up to 15000 frames, 1500 seconds long of 2D, color and PW/CW images for review
- Acquisition, storage and replay of Doppler audio

Compare

- Flexibly compare live imaging with stored imaging by one key

Quick save feature

- The system provides quick save function through USB stick, internal/external HDD, DVD during or after exam
- Configurable saving file format, VRD (Raw Data), DICOM, PNG and AVI

Physio

- One 3-lead ECG input
- Gain, sweep rate and display position controls
- Automatic heart rate calculation and display
- Fault condition display

Archive

- Patient data input which include patient ID, name, nationality, birth date, sex, exam physician, quality check, exam operator
- Physical data such as weight, height
- Patient exam management
- Patient exam images storage and management
- Import VRD format data into the system from outside media, such as USB stick, external HDD, DVD
- Export patient data into outside medias





Report

- Automatically pull patient data into the report
- Automatically load measurement worksheet into the report
- Pull related exams' images into the report
- Write comments in the report
- Print report through network or local printer

Connectivity

- | | |
|---|---|
| <ul style="list-style-type: none"> • Standard connectivity features • Local print to on-board or off-board video printers through USB port • Page report print • Image export to removable media (DVD, external HDD, USB stick) • Network linkage • Image export to network storage servers* • DICOM export and retrieve * • Integrated DVDRW | <ul style="list-style-type: none"> • Support standard DVD media • Data storage formats include VRD, DICOM, JPEG, AVI • VRD and DICOM images stored in disc can be recalled on the system • PNG and AVI images can be played on normal computers • On-board patient exam storage • Direct digital storage of static image or cineloop images to internal hard disk drives • Fully integrated user interface |
|---|---|

Probes/application

- | | |
|---|--|
| <ul style="list-style-type: none"> • Selectable multiple applications • Edit exist application preset • Edit user defined preset | <ul style="list-style-type: none"> • Rename preset • Return to factory preset • Quick save user defined parameters in related application |
|---|--|

Safety Conformance

- Regulatory Notice: This device is tested to meet all applicable requirements in relevant. According to 93/42 EEC, it is class IIa medical device.
- Conformity to Standards:
- IEC 60601-1 E3:2005 Medical electrical equipment - Part 1: General requirements for basic safety and essential performance
- IEC 60601-1-1:2000 Safety requirements for medical electrical systems
- IEC 60601-1-2:2007 Electromagnetic compatibility - Requirements and tests
- IEC 60601-1-4:2000 Programmable electrical medical Systems
- IEC 60601-1-6:2010 Usability
- IEC 60601-2-37:2005 Medical electrical equipment Particular requirements for the safety of ultrasonic medical diagnostic and monitoring equipment
- IEC 61157:2007 Declaration of acoustic output parameters
- ISO 10993-1:2009 Biological evaluation of medical devices
- IEC 62366:2007 Medical devices Application of usability engineering to medical devices
- Council Directive 93/42/EEC on M.D.
- Directive 2002/96/EC on Waste Electrical and Electronic Equipment
- Directive 2006/42/EC on Machinery

Measurement and Analysis

Generic Measurement in 2D mode

- | | | |
|--|--|--|
| <ul style="list-style-type: none"> • Depth • Distance • Perimeter • Length and width method • Ellipse method • Polygon method • Spline method • Tracing method • Area | <ul style="list-style-type: none"> • Length and width method • Ellipse method • Polygon method • Spline method • Tracing method • Volume • Single line method • Dual line method • Triple line method | <ul style="list-style-type: none"> • Single ellipse method • Single ellipse and single line method • Angle • Stenosis • Diameter method • Square meter method • A and B ratio • Diameter ratio • Square meter ratio |
|--|--|--|

Generic Measurement in M mode

- | | | |
|--|---|---|
| <ul style="list-style-type: none"> • Depth • Distance • Time • Speed | <ul style="list-style-type: none"> • Heart rate • Stenosis • A and B ratio | <ul style="list-style-type: none"> • Diameter ratio • Time ratio • Speed ratio |
|--|---|---|



Generic Measurement in PW mode

- Speed (include PV (Peak Velocity))
- Time (include AT (Accelerate Time))
- Acceleration
- PS (Peak Speed in systole period)
- ED (The speed in the end of diastole period)
- MD (Minimum speed in diastole period)
- TAMAX (maximum speed in time average)
- TAMEAN (mean speed in time average)
- TAMIN (minimum speed in time average)
- PI (Pulsatility Index)
- RI (Resistance Index)
- PS and ED ratio
- ED and PS ratio
- A and B ratio (A/B ratio)
- Speed ratio
- Time ratio
- Acceleration ratio
- FLOWVOL (Flow Volume)
- MaxPG (maximum pressure gradient)
- MeanPG (Mean pressure gradient)
- SV (Stroke Volume)
- Each volume diameter cardiac
- Time mean speed in each stroke volume
- Cardiac output
- Heart rate

Abdominal Measurement

- General abdomen
- Difficult abdomen
- Kidney
- Renal vessel
- Abdominal trauma

Small Part Measurement

- Thyroid
- Breast
- Testis
- Musculoskeletal
- Upper and lower extremity joint
- Nerve block

Vessel Measurement

- Carotid artery
- Upper artery
- Upper vein
- Lower artery
- Lower vein
- Vessel puncture
- Transcranial Doppler

Gynecology Measurement

- Uterus and Plevis
- Follicle

Urology Measurement

- Bladder
- Prostate
- Renal
- Kidney and ureter
- Pelvic Floor dysfunction

Pediatric Measurement

- Neonatal Head
- Neonatal Abdomen
- Pediatric Abdomen
- Pediatric Hip
- FAST

Obstetrics Measurement

- OB Early
- OB Mid
- OB Late
- Fetal Heart

Cardiac Measurement

- General
- LV
- MV
- Ao
- AV
- LA
- RV
- TV
- PV
- RA
- System