

## **Easy Operation**

High definition color touch screen, touch tone menu, operation freely.

4,5 minutes per sample.

1-15 samples, Cal 1, Cal 2, OC, ST.

put 5-20ul of blood into the sample cup, and press "START"

### **Expand Capacity**

Remote monitoring, online upgrade, interface to LIS system. Independent TF card, user can copy the sample data to PC easily, and print comprehensive report for each patient.

### **Simple Maintenance**

Full Modular Design.

Automatic washing channel.

Easy to change the chromatography column.





# **TECHNICAL FEATURES**

Model: ES-HGB-600

**Testing Method:** Low pressure iron exchange liquid chromatography

**Testing Item:** Glaycated hemoglobin HbA1c.

**Testing Time:** 3 minutes (reporting), full processing 4,5 minutes.

(including cleaning column and recovery time).

**Testing Parameters**: Precision (CV)  $\leq$  3%, Accuracy (V)  $\leq$  1,50%.

Testing Scope: 5 - 10ul.

**Photometer**: 415nm LED Integral flow colorimeter.

Sampler: 20 Sample position.

**Calibration**: Optional selection of 2 points calibration, optional selection automation.

Equipped with 2 groups of high and low level calibrators.

**Reagent Allocation :** Each standard package includes A, B, C, D eluent,

calibrator and hemolytic agent, pump tubing.

**Display:** 320 x 240 LC Graphic display, displaying real-time testing curve.

**Printer:** 58nm Thermal printer, printing testing curve and report.

Panel: 0-9, YES, NO, START, STOP, ST, PRINT.

Data Storage: 2G TF Card, 100,000 test reports (including Curve).

**USB port**: Support remote upgrading, LIS interface.

PS-2 port : External Barcode Scanner.
Power Supply : AC220V ± 22V, 50Hz ± 1Hz

**Working Environment :** Temperature 10 – 30°C, Relative humidity 30% ~75%

**Size**: 550 x 405 x 347 (mm)

Weight: 12 kg

#### **PERFORMANCE CHARACTERISTICS:**

|          | Within – Ru | Within – Run ( n = 20 ) |      | Inter - Run ( n = 20 ) |  |
|----------|-------------|-------------------------|------|------------------------|--|
| Sample   | Low         | High                    | Low  | High                   |  |
| Mean (%) | 5.58        | 10.24                   | 5.84 | 10.18                  |  |
| SD       | 0.08        | 0.09                    | 0.12 | 0.15                   |  |
| CV       | 1.43        | 0.87                    | 2.13 | 1.47                   |  |





ESSE3 srl, Via Garibaldi 30 14022 Castelnuovo D.B. (AT) Tel +39 011 99 27 706 Fax +39 011 99 27 506 e-mail esse3@chierinet.it

e-mail esse3@chierinet.it web: www.esse3-medical.com

