



# FLECK 9000 SOFTENER

Simple, reliable, and easy-to-use, the Fleck 9000 Meter Alternating Valve is a cost-effective solution for softened water all the time!

Twin tanks provide continuous soft water. With a twin-tank system featuring the new Fleck 9000 valve, families benefit from soft water 24 hours a day, seven days a week. That's because the second tank acts as a backup, ready to immediately provide soft water once 100% of the first tank is used. While the second tank is in service, the first tank regenerates in preparation for the next alternation, giving you all the advantages of continuous soft water

Each 9000 valve is manufactured and machined from cast brass. The 9000 valve has been engineered and tested to withstand the equivalent of 27 years of uninterrupted daily use!

Save money and be more efficient with up to 15% savings in both water and salt consumption over conventional single tank metered systems. Unlike preset single systems, the twin-tank system regenerates with soft water only when necessary. Plus it uses 100% of the softening capacity of tank in service. The end result? Up to fifteen percent savings in both water and salt.\*\*

\*\* Compared to a system with meter delayed regeneration and the reserve set at 30% of the system capacity, provided that half of the reserve capacity is unused

## This Product Includes:

- Fleck 9000 Meter Valve
- Plumbing Adapter (As Chosen From Options)
- Twin 10x54 Mineral Tanks
- 14x34 Square Salt Tank
- 3.00 Cu Ft Hi-Capacity Resin, 8% Crosslink
- Valve-to-Brine Tank Tubing, 6 Ft. x 3/8"
- Brine Tank 2310 Safety Overflow Assembly

## System Specifications:

- Regen Type: Meter Initiated (0-2,100 gal)
- Timer Type: Electro-Mechanical
- Cycle Type: 5-Cycle Adjustable
- Electrical Requirements: 120v/60hz
- Limited Warranty: 5 yrs Valve & 10 yrs Tanks
- Service Flow Rate: 10.90 gpm @ 15 psi Drop
- Backwash Rate: 2.40 gpm
- Dimensions (WxDxH): 20x25x63
- Shipping Weight: 240 lbs



## Option :

- Pre-filter housing
- Filter cartridges ( available 2 , 5 , 10 , 15, 15, 20, 50 , 100 micron )
- Hardness test kit



ESSE 3 Via Garibaldi 30  
14022Castelnuovo D.B. (AT)  
tel +39 011 99 27 706  
fax +39 011 99 27 506  
e-mail [esse3@chierinet.it](mailto:esse3@chierinet.it)  
web : [www.esse3-medical.com](http://www.esse3-medical.com)

